

PROFESSIONAL
SERIES

blackbox™
2-way radios



FEATURES

- ▶ UHF or VHF
- ▶ 16 Channels
- ▶ 5 / 4 / 2 Watts
- ▶ Scanning
- ▶ Voice Channel Enunciation
- ▶ PC Program Freqs, PL, DPL
- ▶ Programmable Buttons:
 - Voice Encryption Function
 - Alarm Function
 - Whisper Transmit Function
 - High/Low Power

NARROWBAND COMPLIANT



Custom Silicone
& Ballistic Nylon
Cases

EarMoldsDirect.net



3.75"

Specifications

General

Frequency Range	UHF: 400-470MHz VHF: 136-174MHz
Channel Capacity	16 (15+S)
Channel Spacing	25.0kHz / 12.5kHz
Frequency Stability	±2.5PPM
Operating Temperature	-25~+55°C
Antenna Impedance	50Ω
Li-ion Battery	1500mAh
Operation Voltage	7.5V
Dimensions (WxHxD)	2.3" x 3.75" x 1.34"
Weight (w/antenna & battery)	6.98 oz or 198g

Transmitter

RF Power (H/L)	UHF: 4W/2W VHF: 5W/2W
----------------	-----------------------

Receiver

Audio Distortion	≤5%
Reference Sensitivity	0.15uV / 0.18uV
Adjacent Channel Selectivity	65dB / 55dB
Intermodulation Reject Ratio	55dB
Audio Power Output	Maximum: ≥0.6W

BANTAM® 2-Way Radio

- Includes battery, rapid charger, antenna, belt clip
- Specify UHF or VHF - programming available



FCC ID: U7GBLACKBOXBU
FCC ID: U7GBLACKBOXBV

CANADA:

IC # 6388A-Bantam UHF
IC # 6388A-Bantam VHF

MEXICO:

IFTTEL-RCPKLB14-0710

